
Valve Body Selection


(for 940E Series Electric Motor Control Valve) $3-WAY \bullet \frac{1}{2}" - 2"$



NLESS S' STAI

All dimensions are nominal. Dimensions in [] are in millimeters.





Trerice 3-Way Valves are not designed for use in steam applications.

Specifications

Action	Body Material	Trim Material	Trim Style	Connection	Pressure & Temperature Rating
Mixing	Stainless steel	Stainless steel	Linear	Threaded	515 PSI @ 400°F (204°C)

Valve Body Selection

				Maximum Close-Off Pressure (psid)							
Valve Body Number	Size Connection Nominal			Actuator Size 25		Actuator Size 26		Dimensions		Approximate	
Number	(NPT)	Port	Cv	Class III	Class IV	Class III	Class IV	E	F	G	Shipping Weight
M18	1/2	1/2"	6.3	238	203	х	х	5.0 [127]	2.8 [71]	2.8 [71]	8 lbs [3.6 kg]
M25	3/4	3/4"	8.2	238	203	х	х	5.0 [127]	2.8 [71]	2.8 [71]	8 lbs [3.6 kg]
M34	1	1"	10	238	203	351	315	5.0 [127]	2.8 [71]	2.8 [71]	8 lbs [3.6 kg]
M56	1 ¹ /2	1 ¹ /2"	20	100	76	151	127	6.1 [155]	3.4 [86]	3.5 [89]	15 lbs [6.8 kg]
M67	2	2"	40	58	39	90	71	6.5 [165]	3.8 [97]	3.8 [97]	19 lbs [8.6 kg]

